

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

## Resin-moulded semiconductor hybrid module and manufacturing method thereof

Patent Number: EP0936671

Publication date: 1999-08-18

Inventor(s): KAMIMURA NORITAKA (JP); TAKAHASHI MASAOKI (JP); SAEKI JUNICHI (JP); TAMBA AKIHIRO (JP); YAMADA KAZUJI (JP); GOUDA MASAHIRO (JP); ISHII MAKOTO (JP); OGAWA TOSHIO (JP); SUZUKI KAZUHIRO (JP)

Applicant(s): HITACHI LTD (JP)

Requested Patent: ☐ EP0936671

Application Number: EP19990101733 19990211

Priority Number (s): JP19980029491 19980212


IPC Classification: H01L25/16; H01L23/433

EC Classification: H01L25/16H, H01L23/433E

Equivalents: ☐ JP11233712, ☐ US6291880

Cited Documents: EP0774782; US5699609; US5077595; JP8298299

### Abstract

A semiconductor device includes a main circuit part having a semiconductor device formed on an electrode plate (13) of a lead frame and a control circuit part having protective functions, which is integrally molded by a resin mold part (30) into an integral mold structure. 

Data supplied from the esp@cenet database - I2